

STILO BOLLARD RAISED

Professional LED Bollard

Concept: Direct emission LED Bollard Luminaire.

Housing: Die-cast aluminum independently sealed LED housing and heat sink.

Materials: Powder coated in ferrite finish anodized extruded aluminum body.

Optics: High efficiency anodized aluminium reflector for floor washer with downward illumination or wall washer with upward illumination beam spreads.

Mounting: 316L grade stainless steel base and stainless steel anti-theft screws (special wrench included).

Installation: Pre-cabled with 6' SJ00W 18-3 cable (second 18-3 plenum cable for 0-10V dimmable version). Fixture is provided with 6ft IP68 connector cable, direct burial brass ingrade jbox (required, sold separately).

Driver: Watertight optical unit with an IP66 plug for rapid connection. IP68 integrated power supply, box fitted with IP68 watertight connectors.

Finish: Ferrite Grey

Dimming: Non-Dimmable, Electronic Phase or 0-10V Dimmable

Wattage: 24W (Floor) and 37W (Wall Washer) standard

Color Temperature: 3000°K / 4000°K

Lumens: **24W** **37W**

3000K = 1341Lm 2374Lm

4000K = 1385Lm 2452Lm

Lumen Maintenance (L70): 50,000hrs

Calculation for LED fixtures are based on measurements that comply with IES LM-80.

CRI: 84

Voltage: Universal Voltage 120-277V AC 50/60Hz

BUG: B1-U3-G1 (FW) B1-U5-G1 (WW)

IK Rating: IK10

IP Rating: IP67

Certifications: cULus listed Wet Location


Tested in accordance with LM-79-08

Warranty: 5 year limited warranty



PRODUCT CODE	TYPE	DRIVER	OPTICS	WATTAGE	COLOR TEMP	CRI
ST — STILO	RS — Raised	ND — Non-Dimmable	FW — Floor Washer	L1 — 24W	30 — 3000K	84 — 84 CRI
		EP — Electronic Phase Dimmable	WW — Wall Washer	L2 — 37W	40 — 4000K	
		10 — 0-10V Dimmable				

Views



TARGETTI


STILO BOLLARD RAISED

ACCESSORIES	
1E3043	Chromatic Filter - Yellow
1E3040	Chromatic Filter - Red
1E3042	Chromatic Filter - Blue
1E3044	Chromatic Filter - Magenta
1E3041	Chromatic Filter - Green




Chromatic Filter

MOUNTING (REQUIRED) - CHOOSE 1	
1E2564	Mounting Plate
CONSULT FACTORY	Ground anchor for direct burial available instead of mounting plate




1E2564



Ground Anchor

INSTALLATION (REQUIRED)	
1DU2530	Direct burial brass ingrade jbox (REQUIRED)
1E2495	Tool - Torx head TX30



1DU2530



1E2495

TARGETTI

STILO BOLLARD RAISED

Photometry

